



備注:

1. 任意10個棘輪孔的累計誤差不超過 $\pm 0.2\text{mm}$ .
2. 載帶長度方向100mm距離的非平行度不可超過1mm.
3. 所有尺寸依國際EIA-481-3標準
4. 材質: 黑色 PS料, 厚度  $0.3 \pm 0.05\text{mm}$ .
5. 表面電阻率 $10^5 \sim 10^{10} \Omega$ .
6. 產品符合ROHS標準。

ITEM	W	A0	B0	K0	P0	P1	P2	F	S	E	D0	T
DIM	$12 \pm 0.30$	$3.30 \pm 0.1$	$3.30 \pm 0.1$	$1.10 \pm 0.1$	$4.0 \pm 0.1$	$8.00 \pm 0.1$	$2.0 \pm 0.1$	$5.5 \pm 0.1$	$0.0 \pm 0.1$	$1.75 \pm 0.1$	$1.5 \pm 0.10$	$0.3 \pm 0.05$

Table 9-2 AXP323 Packing Quantity Information

Type	Quantity	Part Number
Tape	3000pcs/Tape	AXP323

## 9.3 Storage

### 9.3.1 Moisture Sensitivity Level(MSL)

A package's MSL indicates its ability to withstand exposure after it is removed from its shipment bag, a low MSL device sample can be exposed on the factor floor longer than a high MSL device sample. ALL MSL are defined in Table 9-3.

Table 9-3 MSL Summary

MSL	Out-of-bag floor life	Comments
1	Unlimited	$\leq 30^\circ\text{C}/85\%\text{RH}$
2	1 year	$\leq 30^\circ\text{C}/60\%\text{RH}$
2a	4 weeks	$\leq 30^\circ\text{C}/60\%\text{RH}$
3	168 hours	$\leq 30^\circ\text{C}/60\%\text{RH}$
4	72 hours	$\leq 30^\circ\text{C}/60\%\text{RH}$
5	48 hours	$\leq 30^\circ\text{C}/60\%\text{RH}$
5a	24 hours	$\leq 30^\circ\text{C}/60\%\text{RH}$
6	Time on Label(TOL)	$\leq 30^\circ\text{C}/60\%\text{RH}$

AXP323 device samples are classified as MSL3.

### 9.3.2 Bagged Storage Conditions

The shelf life of AXP323 are defined in Table 9-4.